

View Online at <https://aerobasegroup.com/nsn/4820-01-424-9868>

Bolt Hole Quantity:

8 2nd end

Maximum Operating Temp:

650.0 degrees fahrenheit single response

End Application:

Ticonderoga class cg (47)

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

3.000 inches

Adjustable Pressure Range:

+128.0/+145.0 pounds per square inch

Maximum Operating Pressure:

300.0 pounds per square inch single response

Outside Diameter:

7.500 inches 1st end

Thickness:

0.813 inches 2nd end

First Connection Face To Centerline Distance:

4.875 inches

Bolt Hole Diameter:

0.750 inches all ends

Second Connection Face To Centerline Distance:

5.375 inches

Bolt Circle Diameter:

6.000 inches 1st end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

5.000 inches 1st end

Special Features:

Marine service approved

Material:

Stainless steel stem

Material Specification:

Aisi 304 assn standard single material response flow control device

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0