NSN 4820-01-425-2077

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-425-2077

Valve Discharge Flow Rate:
100.0 gallons per minute
End Application:
Ticonderoga class cg (47)
Connection Style:
G4 gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Adjustable Pressure Range:
+500.0/+3000.0 pounds per square inch
Maximum Operating Pressure:
5000.0 pounds per square inch single response
Thread Size:
1.312 inches all ends
Opening Pressure Setting:
Opening Fressure Setting.
1000.0 pounds per square inch
1000.0 pounds per square inch
1000.0 pounds per square inch Special Features:
1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port
1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material:
1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body
1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body Shelf Life:
1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body Shelf Life: N/a
1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body Shelf Life: N/a
1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body Shelf Life: N/a Unit Of Measure:
1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body Shelf Life: N/a Unit Of Measure: Demilitarization:
1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body Shelf Life: N/a Unit Of Measure: Demilitarization: No
1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: