NSN 4820-01-425-2077

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-425-2077

| Valve Discharge Flow Rate: |
|--|
| 100.0 gallons per minute |
| End Application: |
| Ticonderoga class cg (47) |
| Connection Style: |
| G4 gasket sea (boss) all ends |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded internal boss all ends |
| Adjustable Pressure Range: |
| +500.0/+3000.0 pounds per square inch |
| Maximum Operating Pressure: |
| 5000.0 pounds per square inch single response |
| Thread Size: |
| 1.312 inches all ends |
| Opening Pressure Setting: |
| Opening Fressure Setting. |
| 1000.0 pounds per square inch |
| |
| 1000.0 pounds per square inch |
| 1000.0 pounds per square inch Special Features: |
| 1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port |
| 1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: |
| 1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body |
| 1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body Shelf Life: |
| 1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body Shelf Life: N/a |
| 1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body Shelf Life: N/a |
| 1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body Shelf Life: N/a Unit Of Measure: |
| 1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body Shelf Life: N/a Unit Of Measure: Demilitarization: |
| 1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body Shelf Life: N/a Unit Of Measure: Demilitarization: No |
| 1000.0 pounds per square inch Special Features: 1/2 in. Nptf gauge port Material: Iron body Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: |