NSN 4820-01-425-6834

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-425-6834 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends **Disk Loading Method:** Spring Valve Discharge Flow Rate: 30.0 gallons per minute **Maximum Operating Temp:** 250.0 degrees fahrenheit single response **Minimum Operating Temp:** -40.0 degrees fahrenheit **End Application:** 2320-01-354-4528; truck, family of me **Connection Style:** G46d plain (screw-in cartridge) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded cartridge all ends **Adjustable Pressure Range:** +50.0/+5000.0 pounds per square inch **Maximum Operating Pressure:** 5000.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Special Features:** Cartridge type Material: Steel flow control device Media For Which Designed: Fuel/oil, hydrocarbon single response **Style Designator:** Err-090 **Thread Series Designator:** Unf all ends Shelf Life:

N/a
Unit Of Measure:
-Demilitarization:
No

NSN 4820-01-425-6834

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0