NSN 4820-01-426-2468

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-426-2468

Flow Control Device:					
Disk					
Bonnet Type:					
Outside screw-yoke					
Bonnet Attachment Method:					
Bolted					
Bolt Hole Quantity:					
4 all ends					
Maximum Operating Temp:					
100.0 degrees fahrenheit single response					
End Application:					
Mars class afs					
Valve Operation Method:					
Manual					
Flange Shape:					
Round with holes all ends					
Connection Type:					
Flange all ends					
Valve Size:					
1.000 inches					
Maximum Operating Pressure:					
1480.0 pounds per square inch single response					
Outside Diameter:					
4.875 inches all ends					
Face To Face Distance:					
8.500 inches					
Thickness:					
0.688 inches all ends					
Bolt Hole Diameter:					
0.750 inches all ends					
Bolt Circle Diameter:					
3.500 inches all ends					
Flange Face Design:					
Raised straight all ends					
Raised Face Height:					
0.250 inches all ends					
Raised Face Diameter:					
2.125 inches all ends					
Material:					
Steel body					
Style Designator:					

Err-090

NSN 4820-01-426-2468

Globe Valve - Page 2 of 2



Furnis	hed Ite	ems <i>F</i>	And Q	uantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0