

View Online at <https://aerobasegroup.com/nsn/4820-01-426-2469>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

100.0 degrees fahrenheit single response

Minimum Operating Temp:

-20.0 degrees fahrenheit

End Application:

Mars class afs

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

2.000 inches

Maximum Operating Pressure:

250.0 pounds per square inch single response

Outside Diameter:

6.000 inches all ends

Face To Face Distance:

8.000 inches

Thickness:

0.625 inches all ends

Bolt Hole Diameter:

0.750 inches all ends

Bolt Circle Diameter:

4.750 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

3.625 inches all ends

Material:

Plastic polytetrafluoroethylene packing

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0