NSN 4820-01-428-3184

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-428-3184

Pipe Size Accommodated:
0.500 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Union
Maximum Operating Temp:
350.0 degrees fahrenheit single response
End Application:
Used on strategic sealift conversion ships class
Connection Style:
Socket all ends
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe all ends
Maximum Operating Pressure:
150.0 pounds per square inch single response
Material:
Material: Iron flow control device
Iron flow control device
Iron flow control device Material Specification:
Iron flow control device Material Specification: Astm b62 assn standard single material response body
Iron flow control device Material Specification: Astm b62 assn standard single material response body Media For Which Designed:
Iron flow control device Material Specification: Astm b62 assn standard single material response body Media For Which Designed: Steam single response
Iron flow control device Material Specification: Astm b62 assn standard single material response body Media For Which Designed: Steam single response Style Designator:
Iron flow control device Material Specification: Astm b62 assn standard single material response body Media For Which Designed: Steam single response Style Designator: Err-090
Iron flow control device Material Specification: Astm b62 assn standard single material response body Media For Which Designed: Steam single response Style Designator: Err-090 Specification Data:
Iron flow control device Material Specification: Astm b62 assn standard single material response body Media For Which Designed: Steam single response Style Designator: Err-090 Specification Data: 59646-mss sp-80 manufacturers standard
Iron flow control device Material Specification: Astm b62 assn standard single material response body Media For Which Designed: Steam single response Style Designator: Err-090 Specification Data: 59646-mss sp-80 manufacturers standard Specification Or Standard:
Iron flow control device Material Specification: Astm b62 assn standard single material response body Media For Which Designed: Steam single response Style Designator: Err-090 Specification Data: 59646-mss sp-80 manufacturers standard Specification Or Standard: 150 class and b6 figure and 2 type
Iron flow control device Material Specification: Astm b62 assn standard single material response body Media For Which Designed: Steam single response Style Designator: Err-090 Specification Data: 59646-mss sp-80 manufacturers standard Specification Or Standard: 150 class and b6 figure and 2 type Shelf Life:
Iron flow control device Material Specification: Astm b62 assn standard single material response body Media For Which Designed: Steam single response Style Designator: Err-090 Specification Data: 59646-mss sp-80 manufacturers standard Specification Or Standard: 150 class and b6 figure and 2 type Shelf Life: N/a
Iron flow control device Material Specification: Astm b62 assn standard single material response body Media For Which Designed: Steam single response Style Designator: Err-090 Specification Data: 59646-mss sp-80 manufacturers standard Specification Or Standard: 150 class and b6 figure and 2 type Shelf Life: N/a
Iron flow control device Material Specification: Astm b62 assn standard single material response body Media For Which Designed: Steam single response Style Designator: Err-090 Specification Data: 59646-mss sp-80 manufacturers standard Specification Or Standard: 150 class and b6 figure and 2 type Shelf Life: N/a Unit Of Measure:
Iron flow control device Material Specification: Astm b62 assn standard single material response body Media For Which Designed: Steam single response Style Designator: Err-090 Specification Data: 59646-mss sp-80 manufacturers standard Specification Or Standard: 150 class and b6 figure and 2 type Shelf Life: N/a Unit Of Measure: Demilitarization: