NSN 4820-01-430-4136

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-430-4136

Thread Class:
2a all ends
Thread Direction:
Right-hand all ends
End Application:
5895-01-361-3887
Connection Style:
G50 external seat for gasket seal (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external boss all ends
Mounting Facility:
Clamp
Thready Qty Per Inch (tpi):
32 all ends
Thread Size:
0.875 inches all ends
Opening Pressure Setting:
1.0 pounds per square inch
Material:
Aluminum alloy 2011 and stainless steel
Material Specification:
Qq-a-225/3 federal specification 1st material response and astm a-580 or a-313 assn standard 2nd material response
Media For Which Designed:
Vacuum single response
Surface Treatment:
Anodize and passivate
Surface Treatment Specification:
Mil-a-8625, ty ii military specification 1st treatment response and qq-p-35 federal specification 2nd treatment response
Style Designator:
Err-090
Thread Series Designator:
Uns all ends
Furnished Items And Quantity:
1 nut and 1 washer and 1 gasket
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4820-01-430-4136

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.