

View Online at <https://aerobasegroup.com/nsn/4820-01-430-7305>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

600.0 degrees fahrenheit single response

End Application:

Spruance class dd (963)

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal or vertical

Valve Size:

2.000 inches

Maximum Operating Pressure:

900.0 pounds per square inch single response

Thickness:

1.000 inches all ends

First Connection Face To Centerline Distance:

5.750 inches

Bolt Hole Diameter:

0.750 inches all ends

Second Connection Face To Centerline Distance:

5.750 inches

Bolt Circle Diameter:

5.000 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.250 inches all ends

Raised Face Diameter:

3.625 inches all ends

Material:

Nickel alloy 400 body

Material Specification:

Qq-n-286 federal specification single material response stem

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-c-24252 spec.