NSN 4820-01-430-7322

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-430-7322

view Offilite at https://aerobasegroup.com/hist//4020-t
Flow Control Device:
Disk
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Minimum Operating Temp:
-20.0 degrees fahrenheit
End Application:
Whidbey island class Isd
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Facility:
Wafer
Mounting Position:
Horizontal or vertical
Valve Size:
3.000 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
6.000 inches all ends
Face To Face Distance:
1.875 inches
Bolt Circle Diameter:
6.000 inches all ends
Flange Face Design:
Raised straight all ends
Material:
Steel comp 316 flow control device
Media For Which Designed:
Liquid 2nd response
Style Designator:
Straight through flanged ends
Shelf Life:
N/a

NSN 4820-01-430-7322

Check Valve - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A530b0