NSN 4820-01-431-2514

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-431-2514

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 2nd end
Maximum Operating Temp:
800.0 degrees fahrenheit single response
End Application:
Strategic sealift conversion ships class
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Facility:
Bracket
Valve Size:
3.000 inches
Outside Diameter:
7.500 inches 1st end
Thickness:
0.750 inches 1st end
First Connection Face To Centerline Distance:
4.750 inches
Bolt Hole Diameter:
0.875 inches 2nd end
Second Connection Face To Centerline Distance:
4.750 inches
Bolt Circle Diameter:
6.000 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches 2nd end
Raised Face Diameter:
5.000 inches 1st end

NSN 4820-01-431-2514

Safety Relief Valve - Page 2 of 2



Special Features:
Nozzle type
Material:
Stainless steel flow control device
Style Designator:
Err-090
Furnished Items And Quantity:
1 cap
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A046b0