

View Online at <https://aerobasegroup.com/nsn/4820-01-432-0202>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

4.000 inches

Maximum Operating Pressure:

125.0 pounds per square inch single response

Outside Diameter:

9.000 inches all ends

Thickness:

0.940 inches all ends

First Connection Face To Centerline Distance:

5.750 inches

Bolt Hole Diameter:

0.625 inches all ends

Second Connection Face To Centerline Distance:

5.750 inches

Bolt Circle Diameter:

7.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

6.190 inches all ends

Special Features:

Stop check type valve

Material:

Steel body

Material Specification:

Astma216, wcb assn standard single material response body

Style Designator:

Err-090

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0