NSN 4820-01-432-2560

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-432-2560

| Flow Control Device: |
|--|
| Disk |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Bolted |
| Bolt Hole Quantity: |
| 4 all ends |
| Maximum Operating Temp: |
| 450.0 degrees fahrenheit single response |
| Minimum Operating Temp: |
| -20.0 degrees fahrenheit |
| End Application: |
| Strategic sealift conversion ships class |
| Valve Operation Method: |
| Automatic |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Valve Size: |
| 3.000 inches |
| Maximum Operating Pressure: |
| 285.0 pounds per square inch single response |
| Outside Diameter: |
| 5.000 inches 1st end |
| Thickness: |
| 0.940 inches 2nd end |
| First Connection Face To Centerline Distance: |
| 5.125 inches |
| Bolt Hole Diameter: |
| 0.750 inches 2nd end |
| Second Connection Face To Centerline Distance: |
| 4.875 inches |
| Bolt Circle Diameter: |
| 6.000 inches 2nd end |
| Flange Face Design: |
| Raised straight all ends |
| Raised Face Height: |
| 0.062 inches all ends |
| Raised Face Diameter: |
| E 000 inches and and |

5.000 inches 2nd end

NSN 4820-01-432-2560

Safety Relief Valve - Page 2 of 2

Fiig: A046b0



| Material: |
|---|
| Stainless steel stem |
| Material Specification: |
| Asme sa479, type 316 assn standard single material response flow control device |
| Style Designator: |
| Err-090 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |