## NSN 4820-01-432-2993

Angle Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-432-2993

Thread Direction:
Right-hand 2nd end
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 1st end
End Application:
Strategic sealift conversion ships class
Connection Style:
G46c plain (hose) 2nd end
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Threaded external hose 2nd end
Thready Qty Per Inch (tpi):
7-1/2 2nd end
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thread Size:
2.500 inches 2nd end
Outside Diameter:
7.000 inches 1st end
Thickness:
0.562 inches 1st end
Bolt Hole Diameter:
0.750 inches 1st end
Bolt Circle Diameter:
5.500 inches 1st end
Flange Face Design:
Plain 1st end
Material:
Rubber butadiene-acrylonitrile class nbr seat
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090

## NSN 4820-01-432-2993

Angle Valve - Page 2 of 2



Nh 2nd end

**Furnished Items And Quantity:** 

1 cap and 1 chain

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0