NSN 4820-01-432-6588

Butterfly Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-432-6588 **Thread Class:** 2b all ends **Thread Direction:** Right-hand all ends **Bolt Hole Quantity:** 8 all ends **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Minimum Operating Temp:** 0.0 degrees fahrenheit **End Application:** Mars class afs **Valve Operation Method:** Manual Flange Shape: Round with holes all ends **Connection Type:** Flange all ends Valve Size: 6.000 inches Thready Qty Per Inch (tpi): 10 all ends **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Outside Diameter:** 8.750 inches all ends **Face To Face Distance:** 2.120 inches Thickness: 2.120 inches all ends **Bolt Hole Diameter:** 0.750 inches all ends **Bolt Circle Diameter:** 9.500 inches all ends Flange Face Design: Plain all ends **Butterfly Valve Size:**

6.000 inches

Special Features:

10 position locking lever

NSN 4820-01-432-6588

Butterfly Valve - Page 2 of 2

Material:

A046b0



Steel comp 416 stem
Material Specification:
Astm a582, comp 416 assn standard single material response stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: