

View Online at <https://aerobasegroup.com/nsn/4820-01-433-2628>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

775.0 degrees fahrenheit single response

End Application:

Supply class aoe

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Facility:

Bracket

Valve Size:

4.000 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

9.000 inches all ends

Face To Face Distance:

11.500 inches

Thickness:

0.938 inches all ends

Bolt Hole Diameter:

0.625 inches all ends

Bolt Circle Diameter:

7.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.063 inches all ends

Raised Face Diameter:

6.188 inches all ends

Material:

Steel uns k02501 flow control device

Material Specification:

Astm a216, grade wcb assn standard single material response body

Media For Which Designed:

Oil single response

Style Designator:

Err-090

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0