NSN 4820-01-433-2629

Stop-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-433-2629

Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Renewable Seat Ring Type:
Pressed-in
Bolt Hole Quantity:
8 all ends
End Application:
Supply class aoe
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Facility:
Bracket
Mounting Position:
Vertical
Features Provided:
Bonnet packing
Valve Size:
4.000 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
9.000 inches all ends
Face To Face Distance:
11.500 inches
Thickness:
0.938 inches all ends
Bolt Hole Diameter:
0.625 inches all ends
Bolt Circle Diameter:
7.500 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.063 inches all ends

NSN 4820-01-433-2629

Stop-check Valve - Page 2 of 2



Raised Face Diameter:
6.188 inches all ends
Material:
Steel uns k02501 flow control device
Style Designator:
Straight through flanged ends
Furnished Items And Quantity:
1 handwheel
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A530b0