## NSN 4820-01-434-5491

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-434-5491

Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
8 2nd end
Maximum Operating Temp:
450.0 degrees fahrenheit single response
Minimum Operating Temp:
-20.0 degrees fahrenheit
End Application:
Supply class aoe
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Valve Size:
8.000 inches
Adjustable Pressure Range:
+2.0/+9.0 pounds per square inch
Outside Diameter:
13.500 inches 1st end
Thickness:
1.125 inches 1st end
First Connection Face To Centerline Distance:
9.438 inches
Bolt Hole Diameter:
0.875 inches 2nd end
Second Connection Face To Centerline Distance:
9.500 inches
Bolt Circle Diameter:
9.500 inches 2nd end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends

## NSN 4820-01-434-5491

Safety Relief Valve - Page 2 of 2



Raised Face Diameter:
8.500 inches 2nd end
Special Features:
Model 6q8 jos-15-d
Material:
Steel comp 316 stem
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0