## NSN 4820-01-434-6660

Safety Relief Valve - Page 1 of 2

**Flow Control Device:** 

Disk

View Online at https://aerobasegroup.com/nsn/4820-01-434-6660



**Disk Loading Method:** Spring Valve Discharge Flow Rate: 18.0 gallons per minute **Bolt Hole Quantity:** 4 all ends **Maximum Operating Temp:** 500.0 degrees fahrenheit single response **End Application:** Supply class ace Valve Operation Method: Automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends Valve Size: 1.000 inches Adjustable Pressure Range: +56.0/+77.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch single response **Outside Diameter:** 0.500 inches 2nd end Thickness: 0.562 inches 1st end **First Connection Face To Centerline Distance:** 4.000 inches **Bolt Hole Diameter:** 0.625 inches all ends **Second Connection Face To Centerline Distance:** 4.250 inches **Bolt Circle Diameter:** 3.125 inches 1st end Flange Face Design: Raised straight all ends **Raised Face Height:** 0.062 inches all ends **Raised Face Diameter:** 2.000 inches 1st end

## NSN 4820-01-434-6660

Safety Relief Valve - Page 2 of 2



**Special Features:** Incl packing lifting lever Material: Steel comp 316 flow control device Media For Which Designed: Fuel/oil, hydrocarbon single response Style Designator: Err-090 Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A046b0