

View Online at <https://aerobasegroup.com/nsn/4820-01-434-6660>

Flow Control Device:

Disk

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

18.0 gallons per minute

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

500.0 degrees fahrenheit single response

End Application:

Supply class aoe

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Valve Size:

1.000 inches

Adjustable Pressure Range:

+56.0/+77.0 pounds per square inch

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Outside Diameter:

0.500 inches 2nd end

Thickness:

0.562 inches 1st end

First Connection Face To Centerline Distance:

4.000 inches

Bolt Hole Diameter:

0.625 inches all ends

Second Connection Face To Centerline Distance:

4.250 inches

Bolt Circle Diameter:

3.125 inches 1st end

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

2.000 inches 1st end

Special Features:

Incl packing lifting lever

Material:

Steel comp 316 flow control device

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0