## NSN 4820-01-437-1068

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-437-1068

Pipe Size Accommodated:
0.500 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
<b>Bonnet Attachment Method:</b>
Bolted
Disk Loading Method:
Spring
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe all ends
Maximum Operating Pressure:
150.0 pounds per square inch single response
Opening Pressure Setting:
25.0 pounds per square inch
Special Features:
Grade a shock
Material:
Stainless steel stem
Media For Which Designed:
Steam single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Specification Data:
81349-mil-v-20065 government specification
Specification Or Standard:
D composition and 1 type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 4820-01-437-1068

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-v-20065 spec.