## NSN 4820-01-437-4802

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-437-4802
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
100.0 degrees fahrenheit single response
End Application:
Wasp class Ihd
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Facility:
Bracket
Valve Size:
0.500 inches
Maximum Operating Pressure:
285.0 pounds per square inch single response
Opening Pressure Setting:
55.0 pounds per square inch
Outside Diameter:
3.500 inches all ends
Thickness:
0.375 inches all ends
First Connection Face To Centerline Distance:
1.670 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
1 670 inches

**Bolt Circle Diameter:** 

2.375 inches all ends

Flange Face Design:

Raised straight all ends

## NSN 4820-01-437-4802

Safety Relief Valve - Page 2 of 2



Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
1.375 inches all ends
Special Features:
2771
Material:
Steel uns j03002 body
Style Designator:
Err-090
Furnished Items And Quantity
4 nut
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A046b0