NSN 4820-01-438-1047

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-438-1047

Pipe Size Accommodated:
1.250 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
25.0 gallons per minute
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Maximum Operating Pressure:
150.0 pounds per square inch single response
Opening Pressure Setting:
150.0 pounds per square inch
Material:
Steel comp 302 seat
Media For Which Designed:
Liquid single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Specification Data:
81349-mil-v-24332 government specification
Specification Or Standard:
B grade
Shelf Life:
N/a

NSN 4820-01-438-1047

Safety Relief Valve - Page 2 of 2



Unit Of Mea	sure:
-------------	-------

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.