## NSN 4820-01-438-1047

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-438-1047

Pipe Size Accommodated: 1.250 inches all ends Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Union **Disk Loading Method:** Spring Valve Discharge Flow Rate: 25.0 gallons per minute **Renewable Seat Ring Type:** Threaded Maximum Operating Temp: 250.0 degrees fahrenheit single response **Connection Style:** Socket with brazing ring err-100 Valve Operation Method: Automatic **Connection Type:** Unthreaded internal pipe all ends **Features Provided:** Pressure tight outlet side Maximum Operating Pressure: 150.0 pounds per square inch single response **Opening Pressure Setting:** 150.0 pounds per square inch Material: Steel comp 302 seat Media For Which Designed: Liquid single response Style Designator: Err-090 **Furnished Items And Quantity:** 1 lever **Specification Data:** 81349-mil-v-24332 government specification **Specification Or Standard:** B grade Shelf Life:

N/a

## NSN 4820-01-438-1047

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.

