NSN 4820-01-438-6611

Globe Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-438-6611

| Bonnet Type: |
|---|
| Outside screw-yoke |
| Bonnet Attachment Method: |
| Bolted |
| Bolt Hole Quantity: |
| 8 all ends |
| End Application: |
| Stalwart class tagos |
| Valve Operation Method: |
| Manual |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Valve Size: |
| 4.000 inches |
| Maximum Operating Pressure: |
| 225.0 pounds per square inch 2nd response |
| Outside Diameter: |
| 9.000 inches all ends |
| Face To Face Distance: |
| 11.875 inches |
| Thickness: |
| 0.688 inches all ends |
| Bolt Hole Diameter: |
| 0.750 inches all ends |
| Bolt Circle Diameter: |
| 7.500 inches all ends |
| Flange Face Design: |
| Plain all ends |
| Special Features: |
| Stop-check type |
| Material: |
| Nickel alloy flow control device |
| Media For Which Designed: |
| Water-oil-gas 2nd response |
| Style Designator: |
| Err-090 |
| Shelf Life: |
| N/a |
| |

NSN 4820-01-438-6611

Globe Valve - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A046b0