NSN 4820-01-438-9896

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-438-9896

Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Minimum Operating Temp:
-40.0 degrees fahrenheit
End Application:
Engine, aircraft, f117-pw-100 (c-17a)
Connection Style:
G9 plain, optional en (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 2nd end
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+235.0/+450.0 pounds per square inch
Maximum Operating Pressure:
450.0 pounds per square inch single response
Thread Size:
0.375 inches all ends
Material:
Steel comp 303 flow control device
Media For Which Designed:
Oil, hydraulic 2nd response
Style Designator:
Err-090
Thread Series Designator:
Nptf 2nd end
Furnished Items And Quantity:
1 cap
Shelf Life:
N/a

NSN 4820-01-438-9896

Safety Relief Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A046b0