NSN 4820-01-439-5021

Safety Relief Valve - Page 1 of 1

A046b0



View Online at https://aerobasegroup.com/nsn/4820-01-439-5021

Automatic Special Features: Must not exceed 200 cc leakage at 55/60 psig; ball seated at 600 psi during assembly; 2.310 in. Min 2.410 in. Maximum lg Shelf Life: N/a Jnit Of Measure: Cemilitarization:	
Special Features: Must not exceed 200 cc leakage at 55/60 psig; ball seated at 600 psi during assembly; 2.310 in. Min 2.410 in. Maximum lg Shelf Life: N/a Jnit Of Measure: - Demilitarization: No	Valve Operation Method:
Must not exceed 200 cc leakage at 55/60 psig; ball seated at 600 psi during assembly; 2.310 in. Min 2.410 in. Maximum lg Shelf Life: N/a Jnit Of Measure: - Demilitarization: No	Automatic
Shelf Life: N/a Jnit Of Measure: - Demilitarization:	Special Features:
N/a Jnit Of Measure: - Demilitarization:	Must not exceed 200 cc leakage at 55/60 psig; ball seated at 600 psi during assembly; 2.310 in. Min 2.410 in. Maximum Ig
Jnit Of Measure: - Demilitarization:	Shelf Life:
- Demilitarization:	N/a
Demilitarization:	Unit Of Measure:
No	
	Demilitarization:
- iig:	No
	Fiig: