

View Online at <https://aerobasegroup.com/nsn/4820-01-439-6366>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

8 2nd end

End Application:

Usns stalwart class tagos

Valve Operation Method:

Automatic

Flange Shape:

Round with holes 2nd end

Connection Type:

Flange 1st end

Mounting Facility:

Bracket

Valve Size:

4.000 inches

Maximum Operating Pressure:

400.0 pounds per square inch single response

Opening Pressure Setting:

30.0 pounds per square inch

Outside Diameter:

9.000 inches 2nd end

Thickness:

1.250 inches 1st end

Bolt Hole Diameter:

0.875 inches 1st end

Bolt Circle Diameter:

7.500 inches 2nd end

Flange Face Design:

Plain 2nd end

Raised Face Height:

0.062 inches 1st end

Raised Face Diameter:

6.937 inches 1st end

Special Features:

Model 091k-m

Material:

Steel stem or copper alloy stem

Media For Which Designed:

Oil, lubricating, diester base single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0