NSN 4820-01-440-7749

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk Loading Method:

Bolt Hole Quantity:

Disk

Spring

4 all ends



View Online at https://aerobasegroup.com/nsn/4820-01-440-7749

Maximum Operating Temp:
500.0 degrees fahrenheit single response
End Application:
Nimitz class cvn
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.500 inches
Adjustable Pressure Range:
+15.0/+19.0 pounds per square inch
Maximum Operating Pressure:
225.0 pounds per square inch single response
Outside Diameter:
7.000 inches all ends
Thickness:
0.875 inches all ends
First Connection Face To Centerline Distance:
5.500 inches
Bolt Hole Diameter:
0.750 inches all ends
Second Connection Face To Centerline Distance:
5.500 inches
Bolt Circle Diameter:
5.500 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
4.120 inches all ends
Product Name:
2 1/2in relief valve, type 2741-t

NSN 4820-01-440-7749

Safety Relief Valve - Page 2 of 2

Fiig: A046b0



Material:
Steel uns j92600 seat
Material Specification:
Astm a582, comp 303 assn standard single material response stem
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No