## NSN 4820-01-440-7749

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-440-7749

**Flow Control Device:** Disk **Disk Loading Method:** Spring **Bolt Hole Quantity:** 4 all ends **Maximum Operating Temp:** 500.0 degrees fahrenheit single response **End Application:** Nimitz class cvn Valve Operation Method: Automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends Valve Size: 2.500 inches Adjustable Pressure Range: +15.0/+19.0 pounds per square inch Maximum Operating Pressure: 225.0 pounds per square inch single response **Outside Diameter:** 7.000 inches all ends Thickness: 0.875 inches all ends **First Connection Face To Centerline Distance:** 5.500 inches **Bolt Hole Diameter:** 0.750 inches all ends **Second Connection Face To Centerline Distance:** 5.500 inches **Bolt Circle Diameter:** 5.500 inches all ends Flange Face Design: Raised straight all ends **Raised Face Height:** 0.062 inches all ends **Raised Face Diameter:** 4.120 inches all ends **Product Name:** 2 1/2in relief valve, type 2741-t

## NSN 4820-01-440-7749

Safety Relief Valve - Page 2 of 2



Material:

Steel uns j92600 seat

## Material Specification:

Astm a582, comp 303 assn standard single material response stem

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0