NSN 4820-01-441-2873

Globe Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Disk

Bolted



View Online at https://aerobasegroup.com/nsn/4820-01-441-2873

Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
800.0 degrees fahrenheit single response
End Application:
Strategic sealift conversion ships class
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Maximum Operating Pressure:
285.0 pounds per square inch single response
Outside Diameter:
3.500 inches all ends
Face To Face Distance:
4.250 inches
Thickness:
0.440 inches all ends
Bolt Hole Diameter:
0.620 inches all ends
Bolt Circle Diameter:
2.380 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
1.380 inches all ends
Material:
Steel uns k03504 body
Material Specification:
Astm a743, grade ca40 assn standard single material response flow control device

NSN 4820-01-441-2873

Globe Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0