

NSN 4820-01-441-6647 Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-441-6647 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends **Valve Discharge Flow Rate:** 2.0 cubic feet per minute **Maximum Operating Temp:** 250.0 degrees fahrenheit 2nd response **Minimum Operating Temp:** -65.0 degrees fahrenheit **End Application:** Aircraft; e-2c hawkeye **Connection Style:** G43 external seat for gasket seal (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external boss all ends Thready Qty Per Inch (tpi): 12 all ends **Thread Size:** 1.062 inches all ends Seat Angle: 37.0 degrees all ends **Special Features:** O/a lg 4.250 in. Material: Aluminum alloy body

Media For Which Designed:

Fuel/oil, hydrocarbon 2nd response

**Surface Treatment:** 

Anodize

**Style Designator:** 

Err-090

**Thread Series Designator:** 

Un all ends

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## NSN 4820-01-441-6647

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0