## NSN 4820-01-441-9251

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Valve Discharge Flow Rate: 343.0 gallons per minute Bolt Hole Quantity:

**Maximum Operating Temp:** 

300.0 degrees fahrenheit single response

Disk

4 all ends



View Online at https://aerobasegroup.com/nsn/4820-01-441-9251

Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Opening Pressure Setting:
60.0 pounds per square inch
Outside Diameter:
7.500 inches all ends
Thickness:
0.625 inches all ends
First Connection Face To Centerline Distance:
4.625 inches
Bolt Hole Diameter:
0.750 inches all ends
Second Connection Face To Centerline Distance:
4.625 inches
Bolt Circle Diameter:
6.000 inches all ends
Flange Face Design:
Plain all ends
Special Features:
Incl pressure tight cap 1
Material:
Copper alloy body
Media For Which Designed:
Liquid single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever

## NSN 4820-01-441-9251

Safety Relief Valve - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0