NSN 4820-01-442-0524

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-442-0524

| Thread Direction: | |
|---|--|
| Right-hand all ends | |
| Flow Control Device: | |
| Poppet | |
| Bonnet Type: | |
| Inside spring | |
| Bonnet Attachment Method: | |
| Threaded | |
| Disk Loading Method: | |
| Spring | |
| Maximum Operating Temp: | |
| 250.0 degrees fahrenheit single response | |
| Minimum Operating Temp: | |
| -20.0 degrees fahrenheit | |
| End Application: | |
| 4940-01-430-9199; engine, aircraft, f100-pw-100 (f-15a/b/c/d) | |
| Connection Style: | |
| G9 plain, optional en (pipe) all ends | |
| Valve Operation Method: | |
| Automatic | |
| Connection Type: | |
| Threaded internal pipe all ends | |
| Maximum Operating Pressure: | |
| 10500.0 pounds per square inch single response | |
| Thread Size: | |
| 0.500 inches all ends | |
| Opening Pressure Setting: | |
| 2800.0 pounds per square inch | |
| Material: | |
| Stainless steel seat | |
| Media For Which Designed: | |
| Liquid single response | |
| Style Designator: | |
| Err-090 | |
| Thread Series Designator: | |
| Nptf all ends | |
| Furnished Items And Quantity: | |
| 1 locking device | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |

NSN 4820-01-442-0524

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

