## NSN 4820-01-442-5023

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-442-5023

Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Minimum Operating Temp:
-20.0 degrees fahrenheit
End Application:
Seawolf class ssn
Connection Style:
Flareless all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal
Horizontal Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 16 all ends
Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure:
Thready Qty Per Inch (tpi):16 all endsMaximum Operating Pressure:6000.0 pounds per square inch single response
Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size:
Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 0.750 inches all ends
Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Seat Angle:
Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Seat Angle: 24.0 degrees all ends
Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Seat Angle: 24.0 degrees all ends Material:
Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Seat Angle: 24.0 degrees all ends Material: Nickel alloy body
Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Seat Angle: 24.0 degrees all ends Material: Nickel alloy body Media For Which Designed:
Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Seat Angle: 24.0 degrees all ends Material: Nickel alloy body Media For Which Designed: Fuel/oil, hydrocarbon single response
<ul> <li>Thready Qty Per Inch (tpi):</li> <li>16 all ends</li> <li>Maximum Operating Pressure:</li> <li>6000.0 pounds per square inch single response</li> <li>Thread Size:</li> <li>0.750 inches all ends</li> <li>Seat Angle:</li> <li>24.0 degrees all ends</li> <li>Material:</li> <li>Nickel alloy body</li> <li>Media For Which Designed:</li> <li>Fuel/oil, hydrocarbon single response</li> <li>Style Designator:</li> </ul>
Thready Qty Per Inch (tpi): 16 all ends Maximum Operating Pressure: 6000.0 pounds per square inch single response Thread Size: 0.750 inches all ends Seat Angle: 24.0 degrees all ends Material: Nickel alloy body Media For Which Designed: Fuel/oil, hydrocarbon single response Style Designator: Straight thru
Thready Qty Per Inch (tpi):16 all endsMaximum Operating Pressure:6000.0 pounds per square inch single responseThread Size:0.750 inches all endsSeat Angle:24.0 degrees all endsMaterial:Nickel alloy bodyMedia For Which Designed:Fuel/oil, hydrocarbon single responseStyle Designator:Straight thruThread Series Designator:
Thready Qty Per Inch (tpi):16 all endsMaximum Operating Pressure:6000.0 pounds per square inch single responseThread Size:0.750 inches all endsSeat Angle:24.0 degrees all endsMaterial:Nickel alloy bodyMedia For Which Designed:Fuel/oil, hydrocarbon single responseStyle Designator:Straight thruThread Series Designator:Unj all ends

Unit Of Measure:

---

## NSN 4820-01-442-5023

Check Valve - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A530b0

