NSN 4820-01-442-9403

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-442-9403

DISK
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
End Application:
Mars class afs
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.000 inches
Outside Diameter:
6.000 inches 1st end
Thickness:
0.750 inches 1st end
First Connection Face To Centerline Distance:
4.500 inches
Bolt Hole Diameter:
0.750 inches all ends
Second Connection Face To Centerline Distance:
4.130 inches
Bolt Circle Diameter:
4.750 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches 1st end
Raised Face Diameter:
3.620 inches 1st end
Material:
Steel comp 630 flow control device
Material Specification:
Astm a582, type 416 assn standard single material response stem

NSN 4820-01-442-9403

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0