## NSN 4820-01-443-1480

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-443-1480

Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Maximum Operating Temp:
200.0 degrees fahrenheit single response
Minimum Operating Temp:
-40.0 degrees fahrenheit
End Application:
2320-01-354-4529; dump truck
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded cartridge 1st end
Mounting Facility:
Panel
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
3500.0 pounds per square inch single response
Thread Size:
0.875 inches 1st end
Opening Pressure Setting:
5.0 pounds per square inch
Special Features:
Cartridge only; 15 gpm rated flow
Material:
Steel
Media For Which Designed:
Oil, hydraulic single response
Style Designator:
Screw-in cartridge
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-01-443-1480

Check Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A530b0