## NSN 4820-01-443-7592

Globe Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-443-7592

Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
425.0 degrees fahrenheit single response
End Application:
Nimitz class cvn
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Maximum Operating Pressure:
100.0 pounds per square inch single response
Outside Diameter:
6.625 inches all ends
Face To Face Distance:
10.000 inches
Thickness:
0.500 inches all ends
Bolt Hole Diameter:
0.563 inches all ends
Bolt Circle Diameter:
5.500 inches all ends
Flange Face Design:
Plain all ends
Material:
Nickel alloy flow control device
Material Specification:
Qq-n-281 cl a federal specification single material response stem
Media For Which Designed:
Water, salt single response
Style Designator:
Err-090

## NSN 4820-01-443-7592

Globe Valve - Page 2 of 2



Fu	ırnis	hed	Items	And	Quantity:
ıv	เบเบ	IICU	ILCIIIS	AIIU.	Qualitity.

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0