NSN 4820-01-444-6179

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-444-6179

Flow Control Povince
Flow Control Device:
Disk
Valve Discharge Flow Rate:
90.0 gallons per minute
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Strategic sealift conversion ships class
Valve Operation Method:
Automatic
Flange Shape:
Round all ends
Connection Type:
Flange all ends
Valve Size:
2.000 inches
Maximum Operating Pressure:
175.0 pounds per square inch single response
Opening Pressure Setting:
150.0 pounds per square inch
Outside Diameter:
6.000 inches 1st end
Thickness:
0.750 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
3.625 inches 1st end
Material:
Stainless steel stem
Material Specification:
Asme 216 gr wcb assn standard single material response body
Media For Which Designed:
Water, fresh single response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-01-444-6179

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0