NSN 4820-01-445-1755

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-445-1755

Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
8 all ends
Maximum Operating Temp:
100.0 degrees fahrenheit single response
End Application:
Mars class afs
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Facility:
Bracket
Valve Size:
2.000 inches
Maximum Operating Pressure:
1480.0 pounds per square inch single response
Outside Diameter:
6.500 inches all ends
Face To Face Distance:
11.500 inches
Thickness:
1.000 inches all ends
Bolt Hole Diameter:
0.750 inches all ends
Bolt Circle Diameter:
5.000 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.250 inches all ends
Raised Face Diameter:
4.250 inches all ends
Special Features:
Integral hard faced seat; trim 13% cres
Material:

Steel body

NSN 4820-01-445-1755

Globe Valve - Page 2 of 2

Fiig: A046b0



Material Specification:
Astm a105 assn standard all material responses body
Style Designator:
Err-090
Furnished Items And Quantity:
1 handwheel
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No