NSN 4820-01-445-2752

Globe Valve - Page 1 of 2

Bonnet Type:



View Online at https://aerobasegroup.com/nsn/4820-01-445-2752

Inside screw
Bonnet Attachment Method:
Union
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
406.0 degrees fahrenheit 1st response
Minimum Operating Temp:
0.0 degrees fahrenheit
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Facility:
Bracket
Features Provided:
Bonnet packing
Valve Size:
0.500 inches
Maximum Operating Pressure:
225.0 pounds per square inch 2nd response
Outside Diameter:
3.500 inches all ends
Face To Face Distance:
3.312 inches
Thickness:
0.438 inches all ends
Bolt Hole Diameter:
0.625 inches all ends
Bolt Circle Diameter:
2.380 inches all ends
Flange Face Design:
Plain all ends
Special Features:
Rising stem
Material:
Copper alloy
Material Specification:
Astm b62 assn standard all material responses

NSN 4820-01-445-2752

Globe Valve - Page 2 of 2



Media For Which Designed:
Water-oil-gas 2nd response
Style Designator:
Err-090
Furnished Items And Quantity:
1 handwheel
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0