NSN 4820-01-451-2487

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-451-2487 **Thread Direction:** Right-hand all ends **Flow Control Device:** Disk **Disk Loading Method:** Spring **Maximum Operating Temp:** 400.0 degrees fahrenheit single response **Minimum Operating Temp:** -20.0 degrees fahrenheit **End Application:** Strategic sealift conversion ships class **Connection Style:** G9 plain, optional en (pipe) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe 2nd end **Maximum Operating Pressure:** 2000.0 pounds per square inch single response **Thread Size:** 1.000 inches 2nd end **Opening Pressure Setting:** 220.0 pounds per square inch **Special Features:** Carbon stee (phosphated) spring; 0.110 sq.In.Orifice area Material: Steel comp 410 stem **Material Specification:** Astm a479 assn standard single material response flow control device Media For Which Designed: Air 1st response **Style Designator:** Err-090 **Thread Series Designator:** Npt all ends **Furnished Items And Quantity:** 1 lever Shelf Life: N/a

Unit Of Measure:

NSN 4820-01-451-2487

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0