## NSN 4820-01-451-2693

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-451-2693

Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Disk Loading Method:
Spring
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Minimum Operating Temp:
-20.0 degrees fahrenheit
End Application:
Strategic sealift conversion ships class
Connection Style:
G9 plain, optional en (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 2nd end
Maximum Operating Pressure:
2000.0 pounds per square inch single response
Thread Size:
1.000 inches 2nd end
Opening Pressure Setting:
68.0 pounds per square inch
Special Features:
Carbon stee (phosphated) spring; orifice area 0.110 sq.ln.
Material:
Steel comp 410 stem
Material Specification:
Astm a479 assn standard single material response flow control device
Media For Which Designed:
Air 1st response
Style Designator:
Err-090
Thread Series Designator:
Npt all ends
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:

## NSN 4820-01-451-2693

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0