## NSN 4820-01-455-0641

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-455-0641 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 350.0 degrees fahrenheit single response **Minimum Operating Temp:** -20.0 degrees fahrenheit **Connection Style:** G9 plain, optional en (pipe) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal tube all ends **Maximum Operating Pressure:** 10500.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Opening Pressure Setting:** 2800.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.500 inches all ends **Special Features:** Viton o-ring, stainless steel seat and spring included in high pressure relief valve Material: Stainless steel body Media For Which Designed: Air single response **Style Designator:** Err-090 **Thread Series Designator:** Unf all ends Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 4820-01-455-0641

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0