NSN 4820-01-455-0641

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-455-0641

| View Online at https://aerobasegroup.com/nsn/4820-01-455-0641 |
|--|
| Thread Class: |
| 3b all ends |
| Thread Direction: |
| Right-hand all ends |
| Flow Control Device: |
| Poppet |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 350.0 degrees fahrenheit single response |
| Minimum Operating Temp: |
| -20.0 degrees fahrenheit |
| Connection Style: |
| G9 plain, optional en (pipe) all ends |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded internal tube all ends |
| Maximum Operating Pressure: |
| 10500.0 pounds per square inch single response |
| Thread Size: |
| 0.750 inches all ends |
| Opening Pressure Setting: |
| 2800.0 pounds per square inch |
| Outside Diameter Tube Accommodated: |
| 0.500 inches all ends |
| Special Features: |
| Viton o-ring, stainless steel seat and spring included in high pressure relief valve |
| Material: |
| Stainless steel body |
| Media For Which Designed: |
| Air single response |
| Style Designator: |
| Err-090 |
| Thread Series Designator: |
| Unf all ends |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 4820-01-455-0641

Safety Relief Valve - Page 2 of 2

Fiig: A046b0

