NSN 4820-01-455-0868

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-455-0868

View Online at https://aerobasegroup.com/nsn/4820-01-455-0868
Thread Class:
3b all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
350.0 degrees fahrenheit single response
Minimum Operating Temp:
-20.0 degrees fahrenheit
Connection Style:
G9 plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal tube all ends
Maximum Operating Pressure:
10500.0 pounds per square inch single response
Thread Size:
0.750 inches all ends
Opening Pressure Setting:
500.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.500 inches all ends
Special Features:
Viton 0-ring, stainless steel seat and spring included in low pressure relief valve
Material:
Stainless steel body
Media For Which Designed:
Air single response
Style Designator:
Err-090
Thread Series Designator:
Unf all ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Na

No

NSN 4820-01-455-0868

Safety Relief Valve - Page 2 of 2

Fiig: A046b0

