

View Online at <https://aerobasegroup.com/nsn/4820-01-455-1665>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

775.0 degrees fahrenheit single response

End Application:

Valve, glb 2.5 cage 14959; w/s code ja nimitz class cvn

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Facility:

Bracket

Valve Size:

2.500 inches

Maximum Operating Pressure:

450.0 pounds per square inch single response

Outside Diameter:

7.000 inches all ends

Face To Face Distance:

8.500 inches

Thickness:

0.6875 inches all ends

Bolt Hole Diameter:

0.750 inches all ends

Bolt Circle Diameter:

5.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.0625 inches all ends

Raised Face Diameter:

4.125 inches all ends

Special Features:

Material must be asbestos free

Material:

Steel flow control device

Media For Which Designed:

Steam single response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

FiiG:

A046b0