

View Online at <https://aerobasegroup.com/nsn/4820-01-456-1485>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Bolt Hole Quantity:**

4 all ends

**End Application:**

Usns stalwart class taos

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Valve Size:**

3.000 inches

**Maximum Operating Pressure:**

225.0 pounds per square inch 2nd response

**Outside Diameter:**

7.500 inches all ends

**Thickness:**

0.625 inches all ends

**First Connection Face To Centerline Distance:**

4.875 inches

**Bolt Hole Diameter:**

0.750 inches all ends

**Second Connection Face To Centerline Distance:**

4.875 inches

**Bolt Circle Diameter:**

6.000 inches all ends

**Flange Face Design:**

Plain all ends

**Special Features:**

Stop check type angle valve

**Material:**

Nickel alloy flow control device

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Err-090

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0