NSN 4820-01-465-5630

Calibrated Flow Valve - Page 1 of 1

No Fiig: A21100



View Online at https://aerobasegroup.com/nsn/4820-01-465-5630 **Body Material:** Nickel-copper alloy, qq-n-281, class a **Body Style:** Straight thru **Furnished Items:** Union nut and brazing ring Media For Which Designed: Water, salt **First End Connection Type:** Unthreaded internal pipe First End Style Designator: Socket w/brazing ring First End Pipe Size Accommodated: 0.500 inches Second End Relationship With First End: Identical Flow Control Device: Diaphragm **End Connection Quantity: Valve Discharge Flow Rate:** 3.0 gallons per minute **Maximum Inlet Pressure Rating:** 150.0 pounds per square inch **Tempurature Rating:** Between 32.0 degrees fahrenheit and 160.0 degrees fahrenheit **Product Name:** Automatic flow control/balancing valve **Special Features:** Operating pressure differential 15-150 psig; flow tolerance +or- 10 pct; union ends for silver brazing qq-c-390b alloy 836; constant flow regardless of pressure fluctuation; mfg recommends duplex strainer with 1/32" perforations be installed in system upstream of valves Shelf Life: N/a **Unit Of Measure:** Demilitarization: