## NSN 4820-01-465-8309



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-465-8309 **Thread Class:** 2b all ends **Bolt Hole Quantity:** 8 all ends **Maximum Operating Temp:** 55.0 degrees celsius 2nd response **End Application:** E-3a awacs acft **Mounting Facility:** Threaded fastener Thready Qty Per Inch (tpi): 32 all ends **Maximum Operating Pressure:** 15.500 pounds per square inch 1st response **Thread Size:** 0.138 inches all ends **Outside Diameter:** 3.000 inches all ends Thickness: 1.250 inches all ends **Bolt Hole Diameter:** 6.0 millimeters all ends **Raised Face Height:** 1.250 inches all ends **Raised Face Diameter:** 2.500 inches all ends **Special Features:** Electromagnetic interference featured, frequency limits are 150khz to 400mhz; e/i rsip ppl Material: Aluminum body Media For Which Designed: Air single response **Test Data Document:** 97942-589r006 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unc 3rd end Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 4820-01-465-8309

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0